



LEADING THE WAY

EMBLEM Solvent Film Matt Monomeric EasyTac 100

EMBLEM SOFOMAMET100 is a white low tack vinyl film with glossy surface made for temporary decorations indoors. Trouble- and bubble-free application caused by repositionable adhesive.

Typical applications for SOFOMAMET 100 are short-term advertising messages.

Matchcode:	SOFOMAMET100
Material:	PVC film, monomeric
Finish:	matt
Color:	white
Thickness:	100 µm
Adhesive:	transparent, acrylate adhesive, solvent free, repositionable several times
Liner:	siliconized PE liner, 140g/m ² ,
Adhesion:	0,5 - 1 N/25 mm acc. to FTM1 - 24 h (average value)
Lamination:	cool, warm
Temperature resistance:	- 30°C to + 90°C
Application temperature:	more than 10° C
Width of rolls:	54"
Length of rolls:	50 m
Storage:	cool and dry environment, at 15-25°C, 50% rel. humidity
Shelf life:	24 month in original packing

COMPATIBLE INKS:

Eco solvent:	yes	UV:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-9950 · Telefax: +49 41 93-995220
E-Mail: info@dataplot.de · Internet: www.dataplot.de



— LEADING THE WAY —

EMBLEM Solvent Film Matt Monomeric EasyTac 100

Description:

Solvent Film Matt Monomeric EasyTac 100 can be printed on with usual solvent-, eco-solvent-, latex- and UV- inks. The foil can be repositioned repeatedly. The low tack adhesive allows simple processing while mounting and removing the vinyl. The print can be fixed bubble-free by nearly every user.

Processing:

EasyTac adhesive is made for dry adherence. It is repositionable several times. The low tack adhesive allows simple procession and easy removing of air-bubbles.

The film can be removed from smooth and solid surfaces without problems. Please perform test adherences on difficult subsurfaces because different material offers different adhesion. Remains of the adhesive can be removed with Isopropanol easily. Before handling the vinyl clean the surface you want to stick it on from dirt, dust and grease to ensure multiple repositionability.

Insufficient drying of printings has a negative influence on the adhesive. Please make sure that your print has dried completely before you laminate it. So you prevent blistering.

Application:

Typical applications for SOFOMAMET100 are short-term advertising messages, decorations, advertising campaigns at the POS, stickers and labels.